



**Government of India
Ministry of Defence
ORDNANCE PARACHUTE FACTORY
Napier Road, Cantt
Kanpur-208004, Uttar Pradesh**



CENTRALISED VENDOR REGISTRATION CERTIFICATE

This is to certify that M/s KRISHNA ENGINEERING INDUSTRIES, NEW CHHACHHRAULI ROAD JAGADHRI YAMUNANAGAR Haryana is registered at ORDNANCE PARACHUTE FACTORY for following Items.

Sl. No.	Factory / Unit	Item Nomenclature	Initial Date of Registration
1	Ammunition Factory Khadki	BRASS STRIP 0.42 MM - 0.02 MM THICK X 39.5 MM + - 0.25 MM WIDE, HARDNESS 55 TO 75 HV, SPECIFICATION JSS-9535-02-2008 Rev.3. FREE FROM ANISOTROPY DEFECT, THICKNESS VARIATION MAX 0.005 MM ACROSS WIDTH IN A COIL. COIL WEIGHT 8 + - 2 KG.[07]	28-08-2018
2		BRASS STRIP 0.15 MM +- 0.025MM THICK X 19.5 MM +-0.1 MM WIDE TO SPECN IS:410-1977 REAFFIRMED 2006 AMDS 1 DESIGNATION NO. Cu Zn 37, CONDITION HB, HARDNESS 110 HV - 135 HV.[07]	28-08-2018
3		BRASS STRIP 2.03 MM + - 0.025MM THICK X 19.05 MM + - 0.25 MM WIDE , HARDNESS 145 TO 180 HV, SPEECN JSS-9535-02-2008 REV. 3[07]	28-08-2018
4		BRASS STRIPS 1.00 mm + 0.02 mm THICK X 12.00 mm + - 0.25 mm WIDE, 1/4 HARD HARDNESS 70-95 HV, SPECIFICATION JSS-9535-02- 2008 REV. 3 (WT OF COIL 5 TO 7 KG).[07]	28-08-2018
5		BRASS STRIP 0.40 mm + - 0.025 mm THICK X 113 mm + - 0.25 mm WIDE ANNEALED, HARDNESS 55 TO 75 HV, SPECN JSS 9535-02:2008 REV. 3.[07]	28-08-2018

6	BRASS STRIP 0.47 MM + - 0.010 MM THICK X 35.6 MM + - 0.25 MM WIDE.THICKNESS VARIATION ACROSS WIDTH MAXIMUM 0.005MM&0.01mm LENGTHWISE IN A COIL. FREE FROM ANISOTROPY DEFECT. HARDNESS 80+- 10 HV. IN A COIL OF I/D 100 mm APPROX & WEIGHT OF COIL 10 KG+- 3 KG SPECN:JSS-9535-02-2008 REV. 3][07]	28-08-2018
7	BRASS STRIP 0.70 +-0.010MMTHICK X 32.0+-0.25MM WIDE ANNEALED HARDNESS 55 TO 75 HV, GRAIN SIZE 0.035MMTO 0.045MM,VARIATION IN THICKNESS ACCROSS WIDTH NOT TO EXCEED 0.005 MM, TO SPECN JSS 9535-02:2008 REV NO. 3 IN COILS,I/D 100MM APPROX,STRIP LENGTH 20-40 MTR COIL WT.10KG MAX FREE FROM SURFACE BLEMISHES[07]	28-08-2018
8	BRASS STRIP 0.81 MM +- 0.010MM THICK X 35.60MM +-0.25MM WIDE HARDNESS 55 TO 75 HV TO SPECN JSS 9535-02:2008 Rev 3 VARIATION IN THICKNESS SHOULD NOT EXCEED 0.005MM ACROSS WIDTH. MATERIAL SHOULD BE FREE FROM ANISOTROPY DEFECT. COIL WEIGHT TO BE APPROX 10 + - 2 KG[07]	28-08-2018
9	BRASS STRIP 0.56 mm + - 0.025 mm THICK X 16 mm + - 0.25 mm WIDE HARDNESS 110 TO 130 HV, TO SPECN JSS:9535-02: 2008) REV. 3[07]	28-08-2018
10	BRASS STRIP 0.40MM +-0.025MM X 38MM+- 0.25MM WIDE ANNEALED, HARDNESS 55 TO 75 HV SPECN JSS-9535-02 - 2008 Rev. No. 3[07]	28-08-2018
11	BRASS STRIP 0.58 MM PLUS/MINUS 0.025MM THICK X 35.6 MM PLUS/ MINUS 0.25 MM WIDE,ANNEALED HARDNESS 55 TO 75 HV,SPECN- JSS-9535 - 02 - 2008 REV. NO. 3 THICKNESS VARIATION ACROSS WIDTH NOT TO EXCEED 0.005 MM, MATERIAL SHOULD BE FREE FROM ANISOTROPY DEFECT. WEIGHT OF COIL 7 KG MAX. [07]	28-08-2018
12	BRASS STRIP 0.70 mm + - 0.025 mm THICK X 35.6 mm + - 0.25 mm WIDE, ANNEALED, HARDNESS 55 TO 75 HV SPECN JSS 9535-02:2008 Rev. 3 [07]	28-08-2018

13		BRASS STRIP 0.30 mm + - 0.025 mm THICK X 75 mm + - 0.25 mm WIDE, ANNEALED, HARDNESS 55 TO 75 HV TO SPECN - JSS - 9535 - 02 - 2008 REV. 3 TO BE SUPPLIED IN COIL FORM OF I/D 100mm APPROX AND WEIGHT OF COIL TO BE 15 KG MAXIMUM.[07]	28-08-2018
14		BRASS STRIP 0.67MM PLUS MINUS 0.01MM THICK X 7.8MM PLUS 0.00 PLUS 0.30MM WIDE HARDNESS 55 TO 75HV. THICKNESS VARIATION MAX. 0.005MM ACROSS WIDTH AND 0.01MM LENGTH WISE IN A COIL FREE FROM ANISOTROPIC DEFECT SPEC. JSS-9535-02: -2008 REV. 3 WEIGHT OF EACH COIL 4 TO 5.5 KG[07]	28-08-2018
15		70/30, ANNEALED BRASS STRIP OF 21.0 (-)0.2 MM WIDTH & 0.5 (+/-) 0.01MM THICKNESS, BRIGHT, CLEAN & FREE FROM SURFACE FOLDS AS PER SPECIFICATION NO.L3 sec./SPECN/39 DT. 27/9/10[07]	28-08-2018
16		BRASS STRIP 0.51 MM + - 0.025 MM THICK X 34.3 MM + - 0.25 MM WIDE, HARDNESS 110 TO 130 HV, SPECN BS2870-1980, DESIGNATION CZ-107.[07]	28-08-2018
17		BRASS STRIP 0.58 MM +- 0.025MM THICK X 54MM +- 0.25MM WIDE ANNEALED HARDNRSS 55 TO 75 HV SPECN.JSS 9535-2-FEB.82 WITH AMENEMENT NO.1(WEIGHT OF THE COIL SHOULD BE 10 TO 25 KG WITH INTERNAL DIA.100/150 MM).[07]	28-08-2018
18		BRASS STRIP 0.76 MM + - 0.025 MM THICK X 36 MM + - 0.25 MM WIDE ANNEALED, HARDNESS 55 TO 75 HV SPECN JSS-9535 2(FEB 82) WITH AMENDMENT NO 1.[07]	28-08-2018
19		BRASS STRIP 0.81MM # 0.025MM THICK X 64MM # 0.25MM WIDE ANNE ALED HARDNESS 55 TO 75 HV SPECN-JSS-9535-02- 2008 REV 3[07]	28-08-2018
20		BRASS STRIP 0.63MM # 0.013MM THICK X 27MM # 0.25MM WIDE HALF HARD HARDNESS 110 TO 130 HV SPECN JSS-9535 2FEB 82[07]	28-08-2018
21	Ordnance Factory Khamaria	BRASS STRIP 102 X 3 66 MM BS2871 CZ126 LF 0717560694 Description : BRASS STRIP 102 X 3 66 MM BS2871 CZ126 LF 0717560694 [ENR Registration]	04-11-2022
22		BRASS STRIP 25 4X0 63 MM LF 0717560949 Description : BRASS STRIP 25 4X0 63 MM LF 0717560949 [ENR Registration]	23-11-2022

Registration No. : RTKK01780C
Initial Date of Registration : 28-08-2018
Downloaded at : 08/06/2026 04:08 pm

Conditions of Registration:

1. This Registration has been carried out based on self-declared documents furnished by Vendor.
2. Changes, if any, in Address or constitution of the Firm, major Machinery/Equipment or Technology should be intimated to the Registration Authority immediately.
3. The Registration Authority reserves the right to cancel this Registration Certificate at any time.
4. Registration will be valid for 05 years with automatic renewal unless cancelled on account of administrative reasons.

This is a system generated certificate. Hence no separate signature is required.

NOTE: It is only a registration of vendor. It does not grant any special supply status to the Vendor. It is for the purpose of participation in Tender process only.